

Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

| | |
|------------------------|-----------------|
| Creation Date: | 05/09/2018 |
| Datasheet No: | |
| Parker Part No: | 932610Q |
| OEM: | Parker Original |
| OEM Part No: | 15P-1 |

Product Dimensions

| | | | |
|---------------|-------|---------------|------|
| A (mm) | 45.0 | (inch) | 1.77 |
| B (mm) | 25.4 | (inch) | 1.00 |
| D (mm) | 45.0 | (inch) | 1.77 |
| E (mm) | 114.3 | (inch) | 4.50 |



Construction Materials

| | |
|--------------------------------|--|
| Seal(s): | FKM: Fluorocarbon |
| Top Endcap: | Glass reinforced nylon |
| Bottom Endcap: | Glass reinforced nylon |
| Inner Support Cylinder: | Mild steel tin plated |
| Filter Media: | Multilayer fiberglass with epoxy coated mesh on both sides |

Calculated Performance Criteria

| | |
|---|---|
| Differential Pressure (Δp): | bar @ l/min |
| Tested to ISO3968 @ 32 cSt | psi @ gpm |
| Efficiency | >Beta 200 @ 4 microns & greater >Beta 1000 @ 5 microns & greater |
| Minimum Collapse Pressure: | >24 bar |
| Tested to ISO2941 | >350 psi |
| Dirt Holding Capacity acc. to ISO16889 | |