


## Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

|                        |                 |
|------------------------|-----------------|
| <b>Creation Date:</b>  | 02/10/2018      |
| <b>Datasheet No:</b>   |                 |
| <b>Parker Part No:</b> | 932687Q         |
| <b>OEM:</b>            | Parker Original |
| <b>OEM Part No:</b>    | Moduflow        |

### Product Dimensions

|               |       |               |      |
|---------------|-------|---------------|------|
| <b>B (mm)</b> | 45.2  | <b>(inch)</b> | 1.78 |
| <b>D (mm)</b> | 93.7  | <b>(inch)</b> | 3.69 |
| <b>E (mm)</b> | 230.9 | <b>(inch)</b> | 9.09 |



### Construction Materials

|                                |  |
|--------------------------------|--|
| <b>Seal(s):</b>                | NBR: Nitrile   |
| <b>Top Endcap:</b>             | Steel  |
| <b>Bottom Endcap:</b>          | Steel  |
| <b>Outer Support Cylinder:</b> | Steel tin plated   |
| <b>Filter Media:</b>           | Multilayer fiberglass with epoxy coated mesh on both sides |

### Calculated Performance Criteria

|   |   |
|---|---|
| <b>Differential Pressure (<math>\Delta p</math>):</b> | bar @ l/min   |
| <b>Tested to ISO3968 @ 32 cSt</b>                     | psi @ gpm   |
| <b>Efficiency</b>                                     | >Beta 200 @ 5 microns & greater<br>>Beta 1000 @ 7 microns & greater |
| <b>Minimum Collapse Pressure:</b>                     | >5 bar  |
| <b>Tested to ISO2941</b>                              | >73 psi   |
| <b>Dirt Holding Capacity acc. to ISO16889</b>         |   |